

MORGAN PRODUCTS

PNEUMATIC CHEMICAL PUMPS FOR THE GAS AND OIL INDUSTRIES

HD Series Injectors

Model (No Timer)	Plunger Displacement	Pump Ratio	Stroke Length in - cm.	Connections All NPT Input/Output	Maximum Discharge PSI - BAR	Output Per Hour Gal. / Lts.
HD187	.2 cc	10:1	1/2 - 1.27	1/4 -M / 1/8-F	1000 - 68.9	.01 - .12 / .05 - .46
HD187-3K	.2 cc	30:1	1/2 - 1.27	1/4 -M / 1/8-F	3000 - 206	.01 - .12 / .05 - .46
HD187M	.2 cc	10:1	1/2 - 1.27	1/4 -M / 1/8-F	1000 - 68.9	.005 - .12 / .02 - .46
HD187-3KM	.2 cc	30:1	1/2 - 1.27	1/4 -M / 1/8-F	3000 - 206	.005 - .12 / .02 - .46
HD312	1.0 cc	10:1	1.0 - 2.54	1/4 -M / 1/4-F	1000 - 68.9	.06 - .63 / .24 - 2.4
HD312M	1.0 cc	10:1	1.0 - 2.54	1/4 -M / 1/4-F	1000 - 68.9	.01 - .63 / .05 - 2.4
HD312-3K	1.0 cc	30:1	1.0 - 2.54	1/4 -M / 1/4-F	3000 - 206	.06 - .63 / .24 - 2.4
HD312-3KM	1.0 cc	30:1	1.0 - 2.54	1/4 -M / 1/4-F	3000 - 206	.01 - .63 / .05 - 2.4
HD312-5K	1.0 cc	50:1	1.0 - 2.54	1/4 -M / 1/4-F	5000 - 344	.06 - .63 / .24 - 2.4
HD312-5KM	1.0 cc	50:1	1.0 - 2.54	1/4 -M / 1/4-F	5000 - 344	.01 - .63 / .05 - 2.4
HD562	3.5 cc	10:1	1.0 - 2.54	1/2 -M / 1/4-F	1000 - 68.9	.25 - 2.5 / 1 - 9.5
HD562M	3.5 cc	10:1	1.0 - 2.54	1/2 -M / 1/4-F	1000 - 68.9	.06 - 2.5 / .24 - 9.5
HD562-3K	3.5 cc	30:1	1.0 - 2.54	1/2 -M / 1/4-F	3000 - 206	.25 - 2.5 / 1 - 9.5
HD562-3KM	3.5 cc	30:1	1.0 - 2.54	1/2 -M / 1/4-F	3000 - 206	.06 - 2.5 / .24 - 9.5
HD562-5K	3.5 cc	50:1	1.0 - 2.54	1/2 -M / 1/4-F	5000 - 344	.25 - 2.5 / 1 - 9.5
HD562-5KM	3.5 cc	50:1	1.0 - 2.54	1/2 -M / 1/4-F	5000 - 344	.06 - 2.5 / .24 - 9.5
HD1062	12.8 cc	10:1	1.0 - 2.54	3/4-M / 1/2-F	1000 - 68.9	1 - 10.4 / 3.9 - 39
HD1062-3K	12.8 cc	30:1	1.0 - 2.54	3/4-M / 1/2-F	3000 - 206	1 - 10.4 / 3.9 - 39

Notes:

All pumps require [TR1](#) timing relay, [TR2](#) timing relay or electric solenoid valve.

HD1062, HD1062-3K requires [SR1S](#) snap action relay.

Maximum stroke rate for all pumps is 50 SPM. Exception HD2000 35 SPM.

MORGAN PRODUCTS INC. 28103 Ave. Stanford / Valencia, CA 91355

(661) 257-3022 - (800) 421-8910 - FAX (661) 257-3385

E-Mail info@morganproducts.com - Web www.morganproducts.com

MORGAN PRODUCTS

PNEUMATIC CHEMICAL PUMPS FOR THE GAS AND OIL INDUSTRIES

Pneumatic Diaphragm Injectors

Model (No Timer)	Diaphragm Displacement	Pump Ratio	Diaphragm Size in - cm.	Connections All NPT Input/Output	Maximum Discharge PSI - BAR	Output Per Hour Gal. / Lts.
D10-316	.8 cc	1:1	1 - 2.5	1/4 -M / 1/4-M	125 - 8.6	.06 - .63 / .24 - 2.4
D10-PVC	.8 cc	1:1	1 - 2.5	1/4 -M / 1/4-F	125 - 8.6	.06 - .63 / .24 - 2.4
D15-316	6.6 cc	1:1	1.5 / 3.8	1/4 -M / 1/4-M	125 - 8.6	.5 - 5.2 / 2 - 20
D15-PVC	6.6 cc	1:1	1.5 / 3.8	1/4 -M / 1/4-F	125 - 8.6	.5 - 5.2 / 2 - 20
D25-316	21.2 cc	1:1	2.5 / 6.4	1/2 -M / 1/2-M	125 - 8.6	2 - 17 / 6.3 - 63
D25-PVC	21.2 cc	1:1	2.5 / 6.4	1/2 -M / 1/2-F	125 - 8.6	2 - 17 / 6.3 - 63
D40-316	51.0 cc	1:1	4 / 10	3/4 -M / 3/4-M	125 - 8.6	3 - 30 / 11 - 114
D40-PVC	51.0 cc	1:1	4 / 10	3/4 -M / 3/4-F	125 - 8.6	3 - 30 / 11 - 114

Notes:

All pumps require [TR1](#) timing relay, [TR2](#) timing relay or electric solenoid valve.

All pumps are shipped with mounting stand.

Maximum stroke rate for all pumps is 50 SPM.

MORGAN PRODUCTS INC. 28103 Ave. Stanford / Valencia, CA 91355

(661) 257-3022 - (800) 421-8910 - FAX (661) 257-3385

E-Mail info@morganproducts.com - Web www.morganproducts.com

MORGAN PRODUCTS

PNEUMATIC CHEMICAL PUMPS FOR THE GAS AND OIL INDUSTRIES

Pneumatic Chemical Injectors

Model (No Timer)	Plunger Displacement	Pump Ratio	Stroke Length in - cm.	Connections All NPT Input/Output	Maximum Discharge PSI - BAR	Output Per Hour Gal. / Lts.
55DS	.2 cc	54:1	3/4 - 1.91	1/4 -M / 1/4-F	8100 - 558	.01 - .12 / .05 - .46
125DS	.8 cc	31:1	1 - 2.54	1/4 -M / 1/4-F	4650 - 320	.06 - .63 / .24 - 2.4
225DS	.8 cc	69:1	1 - 2.54	1/4 -M / 1/4-F	10000 - 689	.06 - .63 / .24 - 2.4
325DS	.8 cc	122:1	1 - 2.54	1/4 -M / 1/4-F	15000 - 1034	.06 - .63 / .24 - 2.4
425DS	.8 cc	217:1	1 - 2.54	1/4 -M / 1/4-F	15000 - 1034	.06 - .63 / .24 - 2.4
235DS	1.8 cc	31:1	1 - 2.54	1/4 -M / 1/4-F	4650 - 320	.15 - 1.5 / .55 - 5.5
335DS	1.8 cc	54:1	1 - 2.54	1/4 -M / 1/4-F	8100 - 558	.15 - 1.5 / .55 - 5.5
435DS	1.8 cc	97:1	1 - 2.54	1/4 -M / 1/4-F	10000 - 689	.15 - 1.5 / .55 - 5.5
275DS	3.2 cc	17:1	1 - 2.54	1/2 -M / 1/4-F	2550 - 175	.25 - 2.5 / .95 - 9.5
375DS	3.2 cc	31:1	1 - 2.54	1/2 -M / 1/4-F	4650 - 320	.25 - 2.5 / .95 - 9.5
475DS	3.2 cc	54:1	1 - 2.54	1/2 -M / 1/4-F	8100 - 558	.25 - 2.5 / .95 - 9.5
3755DS	7.2 cc	14:1	1 - 2.54	3/4 -M / 1/2-F	2100 - 144	.56 - 5.6 / 2.1 - 21
4755DS	7.2 cc	24:1	1 - 2.54	3/4 -M / 1/2-F	3600 - 248	.56 - 5.6 / 2.1 - 21
3500DS	12.8 cc	8:1	1 - 2.54	3/4 -M / 1/2-F	1200 - 83	1 - 10 / 3.9 - 39
4500DS	12.8 cc	14:1	1 - 2.54	3/4 -M / 1/2-F	2100 - 144	1 - 10 / 3.9 - 39
880DS	19.7 cc	31:1	2 - 5.10	3/4 -M / 1/2-F	4650 - 320	1.1 - 11 / 4.1 - 41
1255DS	40.0 cc	14:1	2 - 5.10	1-1/2-M / 3/4-F	2100 - 144	2.2 - 22 / 8.4 - 84
5500DS	154.0 cc	6:1	3.1 - 7.87	1-1/2-M / 3/4-F	900 - 62	9 - 90 / 34 - 341
8500DS	154.0 cc	14:1	3.1 - 7.87	1-1/2-M / 3/4-F	2100 - 144	9 - 90 / 34 - 341

Notes:

All pumps require [TR1](#) timing relay, [TR2](#) timing relay or electric solenoid valve.

Model 425DS, 435DS, 4755DS and 4500DS pumps require [SR1S](#) snap action relay.

Model 800DS, 1255DS, 5500DS and 8500DS require [SR2S](#) snap action relay.

Maximum stroke rate for all pumps is 50 SPM. Exception 800DS and larger 35 SPM.

MORGAN PRODUCTS INC. 28103 Ave. Stanford / Valencia, CA 91355

(661) 257-3022 - (800) 421-8910 - FAX (661) 257-3385

E-Mail info@morganproducts.com - Web www.morganproducts.com